



## Specifications – Sturd-I-Floor®

**DryMax® high-performance oriented strand board (OSB)** is an excellent choice for sub-floors in residential and light commercial construction applications. Each panel is third-party certified for quality and is rated for Exposure 1 bond durability for protected applications and limited exposure during normal construction delays. DryMax OSB has exceptionally low thickness swell when exposed to moisture, helping to avoid costly and time-consuming joint sanding.

### Available Sizes (Sized for 4' x 8')

<b>Square Edge</b>	3'-11 <sup>7</sup> / <sub>8</sub> " (1.216 m) x 7'-11 <sup>7</sup> / <sub>8</sub> " (2.435 m)
<b>Tongue &amp; Groove</b>	3'-11 <sup>1</sup> / <sub>2</sub> " (1.206 m) x 7'-11 <sup>7</sup> / <sub>8</sub> " (2.435 m)

### Building Code Performance Categories, Panel Thickness

- 19/32 CAT, 0.578" (14.68 mm)
- 23/32 CAT, 0.703" (17.85 mm)

### Specifications

<b>Length/Width Tolerance</b>	±1/16" (±1.6 mm)
<b>Straightness Tolerance</b>	±1/16" (±1.6 mm)
<b>Squareness Tolerance</b>	±1/8" (±3.2 mm)
<b>Testing Agency</b>	APA®–The Engineered Wood Association
<b>Classification</b>	<b>Exposure 1</b> – OSB suitable for uses not permanently exposed to the weather. Panels classified as Exposure 1 are intended to resist the effects of moisture on structural performance as may occur due to construction delays, or other conditions of similar severity.
<b>Code Fire Classification</b>	Class III or C
<b>Flame Spread Rating</b>	76-200, smoke-developed index <450
<b>Building Code Compliance</b>	PS 2-10

### Other Information

<b>Forestry Certification</b>	DryMax OSB panels are made from Forest Stewardship Council® (FSC®) certified wood sources.
<b>NGBS Green Certified</b>	DryMax OSB is Home Innovation NGBS Green Certified for Resource Efficiency and Indoor Environmental Quality. Please visit <a href="http://Homeinnovation.com/Green">Homeinnovation.com/Green</a> for more information.
<b>Product Warranty</b>	DryMax OSB is covered by a Lifetime Limited Warranty. For terms and conditions, please refer to our Lifetime Limited Warranty available at <a href="http://www.builditbetter.com">www.builditbetter.com</a> .



The mark of responsible forestry



**Home Innovation**  
NGBS GREEN CERTIFIED™

RESOURCE EFFICIENCY  
INDOOR ENVIRONMENTAL QUALITY



## Specifications – Sturd-I-Floor®

### International Shipping

To prevent the introduction and spread of plant pests, *ISPM 15: International Standards for Phytosanitary Measures*, requires that internationally shipped solid wood pallets be debarked, treated with heat or fumigated with methyl bromide, and marked with a seal of compliance.

**Pallets made with engineered wood, including DryMax® OSB, are exempt from ISPM 15 regulations.** This is because the process of manufacturing engineered wood destroys any live organisms in the wood. (Source: “Boxes, Crate and Reel Manufacturing”, [www.PerformancePanels.com](http://www.PerformancePanels.com))

### Formaldehyde Emissions

DryMax OSB contains no added urea formaldehyde resins. PS 1 and PS 2 structural panels are exempt from testing by the California Air Resources Board (CARB) in the *Composite Wood Air Toxic Control Measure (ATCM)* and phenolic bonded structural panels are exempt from testing or monitoring by HUD in the *Manufactured Home Construction and Safety Standards*.

### Manufacturing Locations

Location	APA Mill Number	Zip Code	Harvest Radius
Englehart, ONT, CA	530	POJ 1H0	50 miles



Georgia-Pacific Wood Products  
133 Peachtree St., N.E.  
Atlanta, GA 30303  
800-284-5347 [www.builditbetter.com](http://www.builditbetter.com)

DryMax, Georgia-Pacific and the DryMax and Georgia-Pacific logos are trademarks owned by or licensed to Georgia-Pacific Wood Products LLC. APA and Sturd-I-Floor are registered trademarks of APA-The Engineered Wood Association. The FSC logo is a trademark of Forest Stewardship Council. The Home Innovation NGBS Green Certified logo is a trademark of Home Innovation Research Labs.  
©2013 Georgia-Pacific Wood Products LLC. All rights reserved. Rev. 9/13 Lit. Item #621515