

SUSTAINABLE Certified Sourcing

www.sfiprogram.org

FORESTRY INITIATIVE



From ceilings to walls to wainscoting, **Ply-Bead® real wood panels** give the classic look of beaded-board plank paneling without the expense.

Available Types & Sizes (Sized for 4' x 8')

Length (Minimum)7'-11%'' (2.435 m)Width (Minimum)3'-11%'' (1.216 m)Groove Spacing1.6'' on center spacing

Building Code Performance Categories, Panel Thickness

• 11/32 CAT, 0.313" (7.95 mm)

Specifications

Length/Width Tolerance +0, -1/16'' (+0, -1.6 mm), based on 4' or 8' value

Testing Agency APA®-The Engineered Wood Association

Classification Exposure 1 – Plywood suitable for uses not permanently exposed to the weather.

Panels classified as Exposure 1 are intended to resist the effects of moisture on structural performance as may occur due to construction delays, or other conditions of similar severity.

Code Fire Classification Class III or C

Flame Spread Rating 76-200, smoke-developed index <450

Building Code Compliance PS 1-09

Other Information

Forestry Certification Ply-Bead panels are made from Sustainable Forestry

Initiative® (SFI®) certified responsible wood sources.

Plytanium sanded plywood panels contain no added urea formaldehyde resins. Emission levels for certified PS 1 structural panels are exempt by the California Air Resources Board (CARB) in the Composite Wood Air Toxic Control Measure (ATCM) and phenolic bonded structural panels are exempt from testing or monitoring by HUD in the Manufactured Home Construction and

Safety Standards.

Manufacturing Locations

Formaldehyde Emission

Location	APA Mill Number	Zip Code	Harvest Radius
Camden, TX	515	75934	90 miles
Corrigan, TX	516	75939	90 miles
Dudley, NC	348	28333	80 miles
Emporia, VA	230	23847	40 miles
Gurdon, AR	517	71743	60 miles
Madison, GA	404	30650	100 miles
Prosperity, SC	329	29127	80 miles
Taylorsville, MS	282	39168	50 miles



Georgia-Pacific