



SEAM TAPE PLUS

ForceField® Seam Tape Plus is a high-performance polypropylene film with a proprietary adhesive offering excellent durability and tear resistance once installed. Its increased breaking strength and elongation allow for movement, which comes in handy for multi-floor buildings and multi-family structures that must consider external factors like wind. This makes ForceField Seam Tape Plus the preferred seam tape for multi-family and light commercial construction projects greater than two stories.



ADVANTAGES

- Seals seams and joints against air and moisture infiltration
- High-performance polypropylene film
- High-performance film offers excellent tear and impact resistance
- Per ASTM D1970, has over 600% elongation
- Easier to work with than traditional seam tapes
- UV and weather resistant—may be applied in temperatures as low as 20°F
- No release liner, reducing waste on the job site and helping save time during installation

General Product Information

Roll Size	3.5" x 90'
Thickness	Minimum 0.006 inch
Packaging	12 rolls per case

QUICK TIPS

ForceField Seam Tapes from Georgia-Pacific must be used to seal the seams between sheathing panels. Tape substitutions are not covered by the ForceField® Weather Barrier System warranty. It can also be used around flanged windows, penetrations, and over material transitions.



HOW TO INSTALL

Taping the Panel Seams

- Before the application of tape, ensure that the sheathing surface is free from moisture, frost, dirt and other bond-inhibiting materials.
- Center the tape over the panel seam so that a minimum 1" of tape is applied on each side of the panel seam.
- Whenever tape splices occur, a 2" overlap should be used. Sequence tape application such that a shingle lap application is achieved. At T-joints, the tape should overlap by 2".
- Apply firm pressure on the tape with your hand to ensure that a continuous bond is achieved between the tape and the panel surface and to eliminate wrinkles and air bubbles. As a best practice, use a J-roller to roll over the tape after hand application.
- For best performance, do not remove and re-apply tape.
- Tape substitutions for ForceField Seam Tape Plus are not covered by the warranty.

HANDLING & STORAGE

Store in a dry, cool place out of direct sunlight. Recommended two-year shelf life.

LIMITATIONS

- Do not install seam tape in temperatures less than 20°F or if panel surface has frost or ice.
- ForceField Seam Tape Plus is resistant to normal weather conditions. It is not intended for use as a cladding system, long-term outdoor exposure, for immersion in water, and cascading water from an unfinished roof or floor. Water should always be directed away from the ForceField® Weather Barrier System.

WARRANTY

For terms and conditions, please refer to Georgia-Pacific's 10 year transferable* limited warranty for ForceField Weather Barrier System available at warranty.gpforcefield.com.

*transferable to subsequent building owner only

CUSTOMER CARE

Our sales and technical experts are available to assist. Contact your Georgia-Pacific field representative directly, call our GP Technical Hotline at 800-225-6119 or contact us for sales information at **866-249-3639**.

PRODUCT TECHNICAL INFORMATION

TYPICAL CHARACTERISTICS

TEST	RESULTS	METHOD
Tensile Strength	1000 PSI	ASTM D1970
Elongation	600%	ASTM D1970
Tear Strength	100 grams	ASTM D1922
Peel Adhesion	Pass	ASTM D3330
Nail Sealability	Pass	ASTM D1970

TEMPERATURE RESISTANCE & EXPOSURE

Minimum application Temp	20 degrees F (-6.7 degrees C)
Maximum application Temp	180 degrees F (82 degrees C)
Weather exposure	Maximum 180 days for normal weather conditions



Georgia-Pacific Building Products

133 Peachtree Street, N.E., Atlanta, Georgia 30303

GP Technical Hotline: (800) 225-6119

GPForceField.com

Unless otherwise noted, all trademarks are owned by or licensed to Georgia-Pacific Building Products.